



Derwent Paint Pan

Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012 and the Hazardous Products Regulations (HPR) WHMIS 2015

Issue date: 8/27/2021
Revision date: 8/27/2021
Version: 1.0

SECTION 1: Identification

1.1. Identification

Product form : Mixture
Product name : Derwent Paint Pan
Product code : See Section 16

1.2. Recommended use and restrictions on use

Use of the substance/mixture : Paint pans for creative and artistic use.

1.3. Supplier

Distributor

ACCO Brands USA LLC
Four Corporate Drive
Lake Zurich, IL 60047-8997
T 800.222.6462

Distributor

ACCO Brands Canada
7381 Bramalea Road
Mississauga ON, L5S 1C4 - Canada
T 905 364 2600

1.4. Emergency telephone number

Emergency number : 877.740.5015 (Toll free); 303.739.1110 (Outside US)

SECTION 2: Hazard(s) identification

2.1. Classification of the substance or mixture

The hazards listed apply to the liquid/powdered paint component. It is expected that the hazards do not apply during the normal expected use of the product.

GHS classification

Eye Dam. 1

2.2. GHS Label elements, including precautionary statements

GHS labelling

Hazard pictograms (GHS) :



Signal word (GHS) :

Danger

Hazard statements (GHS) :

Causes serious eye damage.

Precautionary statements (GHS) :

Wear protective gloves/protective clothing/eye protection/face protection.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Immediately call a poison center or doctor.

2.3. Other hazards which do not result in classification

No additional information available

2.4. Unknown acute toxicity (GHS US)

Not applicable

Derwent Paint Pan

Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012 and the Hazardous Products Regulations (HPR) WHMIS 2015

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Chemical name / Synonyms	Product identifier	%
Talc	Talc Talc / Magnesium silicate / Talc (containing no asbestos fibers) / Talc (containing no asbestos) / Talc not containing asbestiform fibres / Talc, not containing asbestos / Talc, containing no asbestos fibres / Talc (nonasbestos form) / Talc (non-asbestos form) / Talc, non-fibrous type / Talc, non fibrous / Non-asbestiform talc / Talc (containing no asbestos fibres) / Talc (not containing asbestos) / C.I. 77718 / TALC / Trimagnesium tetrasilicon undecaoxide hydrate / Talc, non-asbestiform / Talc, non-fibrous / Pigment White 26 / Magnesium silicate, hydrous / Talc, not containing mineral fibers (including asbestos) / Asbestiform talc / Talc powder	CAS-No.: 14807-96-6	60 – 70
Naturally occurring substances	Naturally occurring substances Naturally occurring chemical substances	CAS-No.: 999999-99-4	50 – 60
Iron oxide (Fe ₂ O ₃)	Iron oxide (Fe ₂ O ₃) C.I. 77491 / C.I. Pigment Red 101 / Diiron trioxide / Ferric oxide / Iron sesquioxide / Iron(III) oxide / Red Iron Oxide / Rouge / CI 77491 / Iron trioxide / Sienna / Pigment Red 101 / Red iron oxide / Red iron oxide pigment / Iron Oxide Red / Diiron(III) trioxide / Iron oxide / Ferric oxide red / Iron oxide, red	CAS-No.: 1309-37-1	1 – 30
Titanium Dioxide	Titanium Dioxide C.I. 77891 / C.I. Pigment White 6 / Titanium oxide (TiO ₂) / CI 77891 / Titanium(IV) oxide / C.I. Pigment White 7 / Pigment White 6 / Titanium dioxide nanoparticles / Titanium oxide / Titanium dioxide(2)	CAS-No.: 13463-67-7	20 – 30
Aluminum	aluminium powder (stabilised) Aluminium / Aluminium metal / Aluminium, metal / Aluminum metal / Aluminum, elemental / Aluminum, metal / C.I. 77000 / CI 77000 / Aluminium powder (stabilised) / Aluminium powder (stabilized) / Aluminium powder / Pigment Metal 1 / Aluminum powder / Aluminium metal, powder / Aluminium powder (pyrophoric) / aluminum	CAS-No.: 7429-90-5	10 – 20
Carbon black	Carbon black C.I. 77266 / C.I. Pigment Black 6 / C.I. Pigment Black 7 / Lampblack / Vegetable carbon / Microjet Black CW / Pigment Black 7 / Coal soot / Channel black / Bonjet Black CW / D and C Black No. 4 / CARBON BLACK / D and C Black No. 2	CAS-No.: 1333-86-4	10 – 20

Derwent Paint Pan

Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012 and the Hazardous Products Regulations (HPR) WHMIS 2015

Name	Chemical name / Synonyms	Product identifier	%
Alcohols, C16-18, ethoxylated	Alcohols, C16-18, ethoxylated Ceteareth-10 / CETEARETH-10 / Ceteareth-2 / Ethoxylated cetylstearyl alcohol / C16-18 Alcohol reacted with 16 moles ethylene oxides / Polyethylene glycol monoalkyl(C16-18) ether / Polyoxyl 20 cetostearyl ether / Polyoxyethylene cetyl/stearyl ether / Ceteareth-3 / Ceteareth-4 / Ceteareth-5 / Ceteareth-6 / Ceteareth-23 / Ceteareth-34 / Ceteareth-80 / Ceteareth-100 / Ceteareth-24 / Ceteareth-25 / Ceteareth-16 / Ceteareth-17 / Ceteareth-18 / Ceteareth-27 / Ceteareth-28 / Ceteareth-29 / Ceteareth-30 / Ceteareth-33 / Ceteareth-40 / Ceteareth-50 / Ceteareth-55 / Ceteareth-60 / Ceteareth-20 / Ceteareth-22 / Ceteareth-7 / Ceteareth-8 / Ceteareth-9 / Ceteareth-11 / Ceteareth-12 / Ceteareth-13 / Ceteareth-14 / Ceteareth-15 / CETEARETH-29 / CETEARETH-6 / Ceteareth / CETEARETH-9 / Ethoxylated alcohols(C16-18) / CETEARETH-3 / CETEARETH-30 / CETEARETH-33 / CETEARETH-25 / CETEARETH-27 / CETEARETH-34 / CETEARETH-4 / CETEARETH-40 / CETEARETH-5 / CETEARETH-50 / CETEARETH-55 / CETEARETH-60 / CETEARETH-7 / CETEARETH-8 / CETEARETH-80 / CETEARETH-28 / (C16-18) Alkyl alcohol ethoxylate / Alcohols, C16-18 (even numbered), ethoxylated, < 2.5 EO / Tallow alcohol / CETEARETH-100 / CETEARETH-11 / CETEARETH-12 / CETEARETH-13 / CETEARETH-14 / CETEARETH-15 / CETEARETH-16 / CETEARETH-17 / CETEARETH-18 / CETEARETH-2 / CETEARETH-20 / CETEARETH-22 / CETEARETH-23 / CETEARETH-24	CAS-No.: 68439-49-6	1 – 10
Barium sulfate	Barium sulfate Barium sulfate (1:1) / Barium sulphate / Baryta White / C.I. 77120 / C.I. Pigment White 21 / Sulfuric acid, barium salt (1:1) / Sulphuric acid, barium salt / BARIUM SULFATE / Pigment White 21 / CI 77120 / barium sulfate	CAS-No.: 7727-43-7	1 – 5
Alcohols, C6-12, ethoxylated	Alcohols, C6-12, ethoxylated C6-12 ethoxylated alcohols / Ethoxylated alcohols(C6-12)	CAS-No.: 68439-45-2	1 – 3

Comments : The concentrations listed represent actual ranges that result from batch variability.

SECTION 4: First-aid measures

4.1. Description of first aid measures

First-aid measures after inhalation	: Adverse effects not expected from this product. If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing. Get medical advice/attention if you feel unwell.
First-aid measures after skin contact	: If skin irritation occurs: Wash skin with plenty of water. Obtain medical attention if irritation persists.
First-aid measures after eye contact	: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER/doctor.
First-aid measures after ingestion	: Do not induce vomiting without medical advice. Never give anything by mouth to an unconscious person. Get medical advice/attention if you feel unwell.

4.2. Most important symptoms and effects (acute and delayed)

Symptoms/effects after inhalation	: None under normal conditions. May cause irritation to the respiratory tract.
-----------------------------------	--

Derwent Paint Pan

Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012 and the Hazardous Products Regulations (HPR) WHMIS 2015

Symptoms/effects after skin contact	: May cause skin irritation. Repeated exposure may cause skin dryness or cracking.
Symptoms/effects after eye contact	: Causes serious eye damage. Symptoms may include discomfort or pain, excess blinking and tear production, with marked redness and swelling of the conjunctiva. May cause burns.
Symptoms/effects after ingestion	: May be harmful if swallowed. May cause gastrointestinal irritation, nausea, vomiting and diarrhea.

4.3. Immediate medical attention and special treatment, if necessary

Symptoms may be delayed. In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible).

SECTION 5: Fire-fighting measures

5.1. Suitable (and unsuitable) extinguishing media

Suitable extinguishing media	: Use extinguishing media appropriate for surrounding fire.
Unsuitable extinguishing media	: None known.

5.2. Specific hazards arising from the chemical

Fire hazard	: Products of combustion may include, and are not limited to: oxides of carbon.
-------------	---

5.3. Special protective equipment and precautions for fire-fighters

Protection during firefighting	: Keep upwind of fire. Wear full fire fighting turn-out gear (full Bunker gear) and respiratory protection (SCBA).
--------------------------------	--

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures	: Use personal protection recommended in Section 8. Isolate the hazard area and deny entry to unnecessary and unprotected personnel.
------------------	--

6.1.1. For non-emergency personnel

No additional information available

6.1.2. For emergency responders

No additional information available

6.2. Environmental precautions

Prevent entry to sewers and public waters.

6.3. Methods and material for containment and cleaning up

For containment	: Contain and/or absorb spill with inert material (e.g. sand, vermiculite), then place in a suitable container. Do not flush to sewer or allow to enter waterways. Use appropriate Personal Protective Equipment (PPE).
Methods for cleaning up	: Sweep or shovel spills into appropriate container for disposal. Avoid dust formation.

6.4. Reference to other sections

For further information refer to section 8: "Exposure controls/personal protection".

Derwent Paint Pan

Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012 and the Hazardous Products Regulations (HPR) WHMIS 2015

SECTION 7: Handling and storage

7.1. Precautions for safe handling

- Precautions for safe handling : No special measures required if used correctly. Avoid contact with skin and eyes. Avoid breathing dust/fume/gas/mist/vapours/spray. Do not swallow. When using do not eat, drink or smoke.
- Hygiene measures : Wash contaminated clothing before reuse. Always wash hands after handling the product.

7.2. Conditions for safe storage, including any incompatibilities

- Storage conditions : Keep out of the reach of children. Store in a dry, cool and well-ventilated place.
- Maximum storage period : Indefinite
- Storage temperature : Ambient

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Derwent Paint Pan	
No additional information available	
Naturally occurring substances (999999-99-4)	
USA - ACGIH - Occupational Exposure Limits	
ACGIH OEL TWA	2 mg/m ³
Talc (14807-96-6)	
USA - ACGIH - Occupational Exposure Limits	
ACGIH chemical category	Not Classifiable as a Human Carcinogen containing no asbestos fibers
USA - OSHA - Occupational Exposure Limits	
Local name	Talc (not containing asbestos) (Silicates (less than 1% crystalline silica))
OSHA PEL TWA [2]	20 mppcf
Remark (OSHA)	Table Z-3. CAS No. source: eCFR Table Z-1.
Regulatory reference (US-OSHA)	OSHA Annotated Table Z-3 Mineral Dusts
USA - IDLH - Occupational Exposure Limits	
IDLH	1000 mg/m ³ (containing no asbestos and <1% quartz)
USA - NIOSH - Occupational Exposure Limits	
NIOSH REL TWA	2 mg/m ³ (containing no Asbestos and <1% Quartz-respirable dust)
Iron oxide (Fe₂O₃) (1309-37-1)	
USA - ACGIH - Occupational Exposure Limits	
ACGIH chemical category	Not Classifiable as a Human Carcinogen
USA - OSHA - Occupational Exposure Limits	
Local name	Iron oxide fume
OSHA PEL TWA [1]	10 mg/m ³ (fume) 15 mg/m ³ (total dust (Rouge)) 5 mg/m ³ (respirable fraction (Rouge))
Regulatory reference (US-OSHA)	OSHA Annotated Table Z-1

Derwent Paint Pan

Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012 and the Hazardous Products Regulations (HPR) WHMIS 2015

Iron oxide (Fe₂O₃) (1309-37-1)	
USA - IDLH - Occupational Exposure Limits	
IDLH	2500 mg/m ³ (dust and fume)
USA - NIOSH - Occupational Exposure Limits	
NIOSH REL TWA	5 mg/m ³ (dust and fume)
Carbon black (1333-86-4)	
USA - ACGIH - Occupational Exposure Limits	
Local name	Carbon black
ACGIH OEL TWA	3 mg/m ³ (inhalable particulate matter)
Remark (ACGIH)	TLV® Basis: Bronchitis. Notations: A3 (Confirmed Animal Carcinogen with Unknown Relevance to Humans)
ACGIH chemical category	Confirmed Animal Carcinogen with Unknown Relevance to Humans
Regulatory reference	ACGIH 2020
USA - OSHA - Occupational Exposure Limits	
Local name	Carbon black
OSHA PEL TWA [1]	3.5 mg/m ³
Regulatory reference (US-OSHA)	OSHA Annotated Table Z-1
USA - IDLH - Occupational Exposure Limits	
IDLH	1750 mg/m ³
USA - NIOSH - Occupational Exposure Limits	
NIOSH REL TWA	3.5 mg/m ³ 0.1 mg/m ³ (Carbon black in presence of Polycyclic aromatic hydrocarbons)
Aluminum (7429-90-5)	
USA - ACGIH - Occupational Exposure Limits	
ACGIH OEL TWA	1 mg/m ³ (respirable particulate matter)
ACGIH chemical category	Not Classifiable as a Human Carcinogen
USA - OSHA - Occupational Exposure Limits	
OSHA PEL TWA [1]	15 mg/m ³ (total dust) 5 mg/m ³ (respirable fraction)
USA - NIOSH - Occupational Exposure Limits	
NIOSH REL TWA	10 mg/m ³ (total dust) 5 mg/m ³ (respirable dust)
Alcohols, C16-18, ethoxylated (68439-49-6)	
No additional information available	
Alcohols, C6-12, ethoxylated (68439-45-2)	
No additional information available	
Titanium Dioxide (13463-67-7)	
USA - ACGIH - Occupational Exposure Limits	
Local name	Titanium dioxide

Derwent Paint Pan

Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012 and the Hazardous Products Regulations (HPR) WHMIS 2015

Titanium Dioxide (13463-67-7)	
ACGIH OEL TWA	10 mg/m ³
Remark (ACGIH)	TLV® Basis: LRT irr. Notations: A4 (Not classifiable as a Human Carcinogen)
ACGIH chemical category	Not Classifiable as a Human Carcinogen
Regulatory reference	ACGIH 2020
USA - OSHA - Occupational Exposure Limits	
Local name	Titanium dioxide (Total dust)
OSHA PEL TWA [1]	15 mg/m ³ (total dust)
Regulatory reference (US-OSHA)	OSHA Annotated Table Z-1
USA - IDLH - Occupational Exposure Limits	
IDLH	5000 mg/m ³
USA - NIOSH - Occupational Exposure Limits	
NIOSH REL TWA	2.4 mg/m ³ (CIB 63-fine) 0.3 mg/m ³ (CIB 63-ultrafine, including engineered nanoscale)
Barium sulfate (7727-43-7)	
USA - ACGIH - Occupational Exposure Limits	
ACGIH OEL TWA	5 mg/m ³ (inhalable particulate matter, particulate matter containing no asbestos and <1% crystalline silica)
USA - OSHA - Occupational Exposure Limits	
OSHA PEL TWA [1]	15 mg/m ³ (total dust) 5 mg/m ³ (respirable fraction)
USA - NIOSH - Occupational Exposure Limits	
NIOSH REL TWA	10 mg/m ³ (total dust) 5 mg/m ³ (respirable dust)

8.2. Appropriate engineering controls

Appropriate engineering controls : Ensure good ventilation of the work station.
Environmental exposure controls : Avoid release to the environment.

8.3. Individual protection measures/Personal protective equipment

Hand protection:
None necessary under normal conditions of use. Wear gloves if handling large quantities.
Eye protection:
Wear eye protection
Skin and body protection:
None necessary under normal conditions of use.
Respiratory protection:
None necessary under normal conditions of use. In case of insufficient ventilation, wear suitable respiratory equipment. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.

Other information:

Handle in accordance with good industrial hygiene and safety procedures. Do not eat, drink or smoke when using this product.

Derwent Paint Pan

Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012 and the Hazardous Products Regulations (HPR) WHMIS 2015

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Solid
Appearance	: Paint.
Colour	: Various
Odour	: No data available
Odour threshold	: No data available
pH	: No data available
Melting point	: No data available
Freezing point	: No data available
Boiling point	: No data available
Flash point	: No data available
Relative evaporation rate (butylacetate=1)	: No data available
Flammability (solid, gas)	: No data available
Vapour pressure	: No data available
Relative vapour density at 20 °C	: No data available
Relative density	: No data available
Solubility	: No data available
Partition coefficient n-octanol/water	: No data available
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available
Explosive limits	: No data available
Explosive properties	: Not explosive.
Oxidising properties	: Non oxidizing.

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

No dangerous reactions known under normal conditions of use.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid

Heat.

10.5. Incompatible materials

None known.

10.6. Hazardous decomposition products

May include, and are not limited to: oxides of carbon.

Derwent Paint Pan

Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012 and the Hazardous Products Regulations (HPR) WHMIS 2015

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity (oral) : Not classified.
Acute toxicity (dermal) : Not classified.
Acute toxicity (inhalation) : Not classified.

Talc (14807-96-6)	
LD50 oral rat	> 5000 mg/kg bodyweight Animal: rat, Animal sex: male, Guideline: OECD Guideline 423 (Acute Oral toxicity - Acute Toxic Class Method)
LD50 dermal rat	> 2000 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 402 (Acute Dermal Toxicity)
LC50 inhalation rat	> 2.1 mg/l air Animal: rat, Guideline: OECD Guideline 403 (Acute Inhalation Toxicity), Guideline: EU Method B.2 (Acute Toxicity (Inhalation)), Guideline: EPA OPPTS 870.1300 (Acute inhalation toxicity)

Iron oxide (Fe₂O₃) (1309-37-1)	
LD50 oral rat	> 10000 mg/kg

Carbon black (1333-86-4)	
LD50 oral rat	> 15400 mg/kg

Aluminum (7429-90-5)	
LD50 oral rat	> 15900 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 401 (Acute Oral Toxicity)
LC50 inhalation rat	> 0.888 mg/l air Animal: rat, Animal sex: male, Guideline: OECD Guideline 403 (Acute Inhalation Toxicity)

Alcohols, C16-18, ethoxylated (68439-49-6)	
LD50 oral rat	1260 mg/kg
ATE CA (oral)	1260 mg/kg bodyweight

Titanium Dioxide (13463-67-7)	
LD50 oral rat	> 5000 mg/kg bodyweight Animal: rat, Animal sex: female, Guideline: OECD Guideline 425 (Acute Oral Toxicity: Up-and-Down Procedure), Guideline: EPA OPPTS 870.1100 (Acute Oral Toxicity)
LC50 inhalation rat	5.09 mg/l/4h
ATE CA (vapours)	5.09 mg/l/4h
ATE CA (dust,mist)	5.09 mg/l/4h

Barium sulfate (7727-43-7)	
LD50 oral rat	307000 mg/kg
ATE CA (oral)	307000 mg/kg bodyweight

Skin corrosion/irritation : Not classified.
Serious eye damage/irritation : Causes serious eye damage.
Respiratory or skin sensitisation : Not classified.
Germ cell mutagenicity : Not classified.
Carcinogenicity : Not classified.

Talc (14807-96-6)	
IARC group	3 - Not classifiable
National Toxicology Program (NTP) Status	Evidence of Carcinogenicity

Derwent Paint Pan

Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012 and the Hazardous Products Regulations (HPR) WHMIS 2015

Iron oxide (Fe ₂ O ₃) (1309-37-1)	
IARC group	3 - Not classifiable
Barium sulfate (7727-43-7)	
NOAEL (chronic, oral, animal/male, 2 years)	60 mg/kg bodyweight Animal: rat, Animal sex: male, Remarks on results: other:Effect type: carcinogenicity (migrated information)
NOAEL (chronic, oral, animal/female, 2 years)	75 mg/kg bodyweight Animal: rat, Animal sex: female, Remarks on results: other:Effect type: carcinogenicity (migrated information)

Reproductive toxicity : Not classified.

Aluminum (7429-90-5)	
NOAEL (animal/male, F0/P)	1000 mg/kg bodyweight Animal: rat, Animal sex: male, Guideline: OECD Guideline 422 (Combined Repeated Dose Toxicity Study with the Reproduction / Developmental Toxicity Screening Test)

STOT-single exposure : Not classified.

STOT-repeated exposure : Not classified.

Talc (14807-96-6)	
NOAEL (oral, rat, 90 days)	100 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 452 (Chronic Toxicity Studies)

Aluminum (7429-90-5)	
LOAEC (inhalation, rat,dust/mist/fume, 90 days)	0.05 mg/l air Animal: rat, Guideline: OECD Guideline 413 (Subchronic Inhalation Toxicity: 90-Day Study)
NOAEL (subchronic, oral, animal/male, 90 days)	1034 mg/kg bodyweight Animal: dog, Animal sex: male, Guideline: OECD Guideline 409 (Repeated Dose 90-Day Oral Toxicity Study in Non-Rodents)
NOAEL (subchronic, oral, animal/female, 90 days)	1087 mg/kg bodyweight Animal: dog, Animal sex: female, Guideline: OECD Guideline 409 (Repeated Dose 90-Day Oral Toxicity Study in Non-Rodents)

Aspiration hazard : Not classified.

Symptoms/effects after inhalation : None under normal conditions. May cause irritation to the respiratory tract.

Symptoms/effects after skin contact : May cause skin irritation. Repeated exposure may cause skin dryness or cracking.

Symptoms/effects after eye contact : Causes serious eye damage. Symptoms may include discomfort or pain, excess blinking and tear production, with marked redness and swelling of the conjunctiva. May cause burns.

Symptoms/effects after ingestion : May be harmful if swallowed. May cause gastrointestinal irritation, nausea, vomiting and diarrhea.

Other information : Likely routes of exposure: ingestion, inhalation, skin and eye.

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general : May cause long-term adverse effects in the aquatic environment.

Talc (14807-96-6)	
LC50 - Fish [1]	> 100 g/l (Exposure time: 96 h - Species: Brachydanio rerio [semi-static])
LC50 - Fish [2]	110000 mg/l Test organisms (species): other:
NOEC (chronic)	1459798 mg/l Test organisms (species): other: Duration: '30 d'

Iron oxide (Fe ₂ O ₃) (1309-37-1)	
LC50 - Fish [1]	100000 mg/l (Exposure time: 96 h - Species: Danio rerio [static])
EC50 - Crustacea [1]	> 100 mg/l Test organisms (species): Daphnia magna

Derwent Paint Pan

Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012 and the Hazardous Products Regulations (HPR) WHMIS 2015

Titanium Dioxide (13463-67-7)	
LC50 - Fish [1]	155 mg/l Test organisms (species): other:Japanese Medaka
EC50 - Crustacea [1]	19.3 mg/l Test organisms (species): Daphnia magna
EC50 - Other aquatic organisms [1]	> 100 mg/l Test organisms (species):
EC50 - Crustacea [2]	27.8 mg/l Test organisms (species): Daphnia magna
LOEC (chronic)	5 mg/l Test organisms (species): Daphnia magna Duration: '21 d'
NOEC (chronic)	≥ 2.92 mg/l Test organisms (species): Daphnia magna Duration: '21 d'

12.2. Persistence and degradability

Derwent Paint Pan	
Persistence and degradability	Not established.

12.3. Bioaccumulative potential

Derwent Paint Pan	
Bioaccumulative potential	Not established.

Talc (14807-96-6)	
BCF - Fish [1]	(no known bioaccumulation)

12.4. Mobility in soil

No additional information available

12.5. Other adverse effects

Other information : No other effects known.

SECTION 13: Disposal considerations

13.1. Disposal methods

Product/Packaging disposal recommendations : Dispose in a safe manner in accordance with local/national regulations.

SECTION 14: Transport information

Department of Transportation (DOT) and Transportation of Dangerous Goods (TDG)

14.1. UN number

Not regulated for transport

14.2. UN proper shipping name

Not regulated for transport

14.3. Transport hazard class(es)

Not regulated for transport

14.4. Packing group

Not regulated for transport

Derwent Paint Pan

Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012 and the Hazardous Products Regulations (HPR) WHMIS 2015

14.5. Environmental hazards

Other information : No supplementary information available.

14.6. Special precautions for user

Special transport precautions : Do not handle until all safety precautions have been read and understood.

14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable

SECTION 15: Regulatory information

15.1. US Federal regulations

All components of this product are listed, or excluded from listing, on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory.

Naturally occurring substances	CAS-No. 999999-99-4
--------------------------------	---------------------

All components of this product are listed, or excluded from listing, on the Canadian DSL (Domestic Substances List) and NDSL (Non-Domestic Substances List) inventories except for:

Naturally occurring substances	CAS-No. 999999-99-4
--------------------------------	---------------------

15.2. International regulations

No additional information available

15.3. US State regulations

California Proposition 65 - This product does not contain any substances known to the state of California to cause cancer, developmental and/or reproductive harm

SECTION 16: Other information

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012 and the Hazardous Products Regulations (HPR) WHMIS 2015

Revision date : 08/27/2021

Other information : None.

Prepared by : Nexreg Compliance Inc.

www.Nexreg.com



Product code

Sets:

2302636 (Inktense Paint Pan Set of 12 Palette #1),
2305544 (Inktense Paint Pan Set of 12 Palette #2 (old)),
2305545 (Inktense Paint Pan Set of 24),
2305657 (Metallic Paint Pan Set of 12),
2305768 (A4 Watercolour Pad + Inktense Paint Pan Set of 12),
2305789 (Inktense Paint Pan Set of 12 Palette #2),
2305790 (Graphitint Paint Pan Set of 12),
2305865 (Pastel Shades Paint Pan Set of 12),
2305866 (Line & Wash Paint Pan Set of 12),
2305872 (Tinted Charcoal Paint Pan Set of 12),
2305903 (Shade & Tone Mixed Media Set)

Individual Colours:

Derwent Paint Pan

Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012 and the Hazardous Products Regulations (HPR) WHMIS 2015

2302623 (Inktense Paint Pan Sun Yellow),
2302624 (Inktense Paint Pan Mango),
2302625 (Inktense Paint Pan Poppy Red),
2302626 (Inktense Paint Pan Dark Plum),
2302627 (Inktense Paint Pan Mid Ultramarine),
2302629 (Inktense Paint Pan Bright Blue),
2302630 (Inktense Paint Pan Racing Green),
2302631 (Inktense Paint Pan Teal Green),
2302632 (Inktense Paint Pan Kiwi),
2302633 (Inktense Paint Pan Burnt Yellow Ochre),
2302634 (Inktense Paint Pan Natural Brown),
2302635 (Inktense Paint Pan Ink Black),
2305546 (Inktense Paint Pan Refill Sherbet Lemon),
2305547 (Inktense Paint Pan Tangerine),
2305548 (Inktense Paint Pan Scarlet),
2305549 (Inktense Paint Pan Fuchsia),
2305550 (Inktense Paint Pan Navy Blue),
2305551 (Inktense Paint Pan French Ultramarine),
2305552 (Inktense Paint Pan Turquoise),
2305553 (Inktense Paint Pan Ionian Green),
2305554 (Inktense Paint Pan Light Olive),
2305555 (Inktense Paint Pan Red Oxide),
2305556 (Inktense Paint Pan Sepia Ink),
2305557 (Inktense Paint Pan Antique White),
2305659 (Metallic Paint Pan Silver),
2305660 (Metallic Paint Pan Graphite),
2305661 (Metallic Paint Pan Pale Gold),
2305662 (Metallic Paint Pan Gold),
2305663 (Metallic Paint Pan Sunset),
2305664 (Metallic Paint Pan Green),
2305665 (Metallic Paint Pan Blue),
2305666 (Metallic Paint Pan Ice Blue),
2305667 (Metallic Paint Pan Purple),
2305668 (Metallic Paint Pan Pink),
2305669 (Metallic Paint Pan Red),
2305670 (Metallic Paint Pan Lime Gold),
2305775 (Inktense Paint Pan Cherry),
2305776 (Inktense Paint Pan Bright Orange),
2305777 (Inktense Paint Pan Violet),
2305778 (Inktense Paint Pan Hookers Green),
2305779 (Inktense Paint Pan Paynes Grey),
2305791 (Graphitint Paint Pan Port),
2305792 (Graphitint Paint Pan Juniper),
2305793 (Graphitint Paint Pan Aubergine),
2305794 (Graphitint Paint Pan Dark Indigo),
2305795 (Graphitint Paint Pan Steel Blue),
2305796 (Graphitint Paint Pan Ocean Blue),
2305797 (Graphitint Paint Pan Slate Green),
2305798 (Graphitint Paint Pan Green Grey),
2305799 (Graphitint Paint Pan Meadow),
2305800 (Graphitint Paint Pan Russet),
2305801 (Graphitint Paint Pan Autumn Brown),

Derwent Paint Pan

Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012 and the Hazardous Products Regulations (HPR) WHMIS 2015

2305802 (Graphitint Paint Pan Graphite Grey),
2305904 (Pastel Paint Pan Lemon),
2305905 (Pastel Paint Pan Peach),
2305906 (Pastel Paint Pan Coral Pink),
2305907 (Pastel Paint Pan Pink Flamingo),
2305908 (Pastel Paint Pan Orchid Pink),
2305909 (Pastel Paint Pan Lavender),
2305910 (Pastel Paint Pan Cornflower),
2305911 (Pastel Paint Pan Turquoise),
2305912 (Pastel Paint Pan Mint),
2305913 (Pastel Paint Pan Artichoke),
2305914 (Pastel Paint Pan Storm Grey),
2305915 (Pastel Paint Pan Silver Blue),
2305928 (Tinted Charcoal Paint Pan Dark Moss),
2305929 (Tinted Charcoal Paint Pan Forest Pine),
2305930 (Tinted Charcoal Paint Pan Driftwood),
2305931 (Tinted Charcoal Paint Pan Mountain Blue),
2305932 (Tinted Charcoal Paint Pan Ocean Deep),
2305933 (Tinted Charcoal Paint Pan Thistle),
2305934 (Tinted Charcoal Paint Pan Glowing Embers),
2305935 (Tinted Charcoal Paint Pan Burnt Embers),
2305936 (Tinted Charcoal Paint Pan Burnt Earth),
2305937 (Tinted Charcoal Paint Pan Natural),
2305938 (Tinted Charcoal Paint Pan Dark),
2305939 (Tinted Charcoal Paint Pan White),
2305943 (Inktense Paint Pan Sepia (Red)),
2305944 (Inktense Paint Pan Venetian Red),
2305945 (Inktense Paint Pan Sanguine),
2305946 (Inktense Paint Pan Mars Orange)

Disclaimer: We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind. The information contained in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. It is the user's responsibility to satisfy oneself as to the suitability and completeness of this information for the user's own particular use.