

Page 1/9

Safety data sheet according to 1907/2006/EC

Printing date 06.12.2022 Version: 1.2 (replaces version 1.1) Revision: 06.12.2022

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- · 1.1 Product identifier
- · Trade name: PROTECTING SPRAY 680, aerosol
- · Article number: 95165680; 95166680
- · UFI: O740-K010-900C-3CHY
- · 1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant identified use: Picture varnish

1.3 Manufacturer/Supplier:

Manufacturer: Royal Talens P.O. Box 4

NL-7300 AA Apeldoorn Tel. +31 (0)55 5274700

UK Distributor: R.Talens UK Ltd P.O. Box 3717 Wokingham RG40 9RS, UK Tel +44 (0)800 995 6500

· Further information obtainable from:

Regulatory Affairs safety@royaltalens.com

· 1.4 Emergency telephone number:

Great Britain: National Poisons Information Service (Birmingham) tel. (44) (0) 1215074123

Ireland: National Poisons Information Centre (Dublin) tel. 35 3 18379966

SECTION 2: Hazards identification

- · 2.1 Classification of the substance or mixture
- · Classification according to Regulation (EC) No 1272/2008



Aerosol 1 H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.



Eye Irrit. 2 H319 Causes serious eye irritation.

STOT SE 3 H336 May cause drowsiness or dizziness.

Aquatic Chronic 3 H412 Harmful to aquatic life with long lasting effects.

· Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the GB CLP regulation.

(Contd. on page 2)

Printing date 06.12.2022 Version: 1.2 (replaces version 1.1) Revision: 06.12.2022

(Contd. of page 1)

· Hazard pictograms



· Signal word Danger

Hazard-determining components of labelling:

Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics propan-2-ol

Hydrocarbons, C9, aromatics

· Hazard statements

H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.

H319 Causes serious eye irritation.H336 May cause drowsiness or dizziness.

H412 Harmful to aquatic life with long lasting effects.

· Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P103 Read carefully and follow all instructions.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

smoking.

P211 Do not spray on an open flame or other ignition source.

P251 Do not pierce or burn, even after use.

P261 Avoid breathing dust/fume/gas/mist/vapours/spray.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

P405 Store locked up.

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

P501 Dispose of contents/container in accordance with local/regional/national/international

regulations.

Additional information:

EUH066 Repeated exposure may cause skin dryness or cracking.

- · 2.3 Other hazards
- · Results of PBT and vPvB assessment
- · **PBT:** Not applicable. · **vPvB:** Not applicable.

SECTION 3: Composition/information on ingredients

· 3.2 Mixtures

· **Description:** Mixture of substances listed below with non-hazardous additions.

· Dangerous components:		
EC/List number: 919-857-5 Reg.nr.: 01-2119463258-33	Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics Flam. Liq. 3, H226; Asp. Tox. 1, H304; STOT SE 3, H336, EUH066	30-50%
CAS: 74-98-6 EINECS: 200-827-9 Reg.nr.: 01-2119486944-21	propane Flam. Gas 1A, H220; Press. Gas (Comp.), H280	10-20%
CAS: 106-97-8 EINECS: 203-448-7 Reg.nr.: 01-2119474691-32	butane, pure Flam. Gas 1A, H220; Acute Tox. 3, H331; Press. Gas (Comp.), H280	10-20%
CAS: 67-63-0 EINECS: 200-661-7 Reg.nr.: 01-2119457558-25	propan-2-ol Flam. Liq. 2, H225; Eye Irrit. 2, H319; STOT SE 3, H336	10-20%
	(Conto	d. on page 3

GB

Version: 1.2 (replaces version 1.1) Printing date 06.12.2022 Revision: 06.12.2022

(Contd. of page 2)

5-10%

CAS: 64742-95-6 Hydrocarbons, C9, aromatics

Additional information: For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

- · 4.1 Description of first aid measures
- · After inhalation: Supply fresh air; consult doctor in case of complaints.
- · After eye contact: Rinse opened eye for several minutes under running water. Then consult a doctor.
- · After swallowing: If symptoms persist consult doctor.
- 4.2 Most important symptoms and effects, both acute and delayed May cause drowsiness or dizziness.
- · 4.3 Indication of any immediate medical attention and special treatment needed No further relevant information available.

SECTION 5: Firefighting measures

- · 5.1 Extinguishing media
- · Suitable extinguishing agents: CO2, sand, extinguishing powder. Do not use water.
- · For safety reasons unsuitable extinguishing agents: Water with full jet
- 5.2 Special hazards arising from the substance or mixture No further relevant information available.
- · 5.3 Advice for firefighters
- · Protective equipment: No special measures required.

SECTION 6: Accidental release measures

· 6.1 Personal precautions, protective equipment and emergency procedures

Keep away from ignition sources.

- 6.2 Environmental precautions: Do not allow product to reach sewage system or any water course.
- · 6.3 Methods and material for containment and cleaning up:

Ensure adequate ventilation.

Do not flush with water or aqueous cleansing agents

· 6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

· 7.1 Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Open and handle receptacle with care.

· Information about fire - and explosion protection:

Do not spray onto a naked flame or any incandescent material.

Keep ignition sources away - Do not smoke.

Protect from heat.

Protect against electrostatic charges.

Pressurised container: protect from sunlight and do not expose to temperatures exceeding 50°C, i.e. electric lights. Do not pierce or burn, even after use.

- · 7.2 Conditions for safe storage, including any incompatibilities
- Storage:
- Requirements to be met by storerooms and receptacles:

Store in a cool location.

Observe official regulations on storing packagings with pressurised containers.

· Information about storage in one common storage facility: Not required.

(Contd. on page 4)

Printing date 06.12.2022 Version: 1.2 (replaces version 1.1) Revision: 06.12.2022

(Contd. of page 3)

· Further information about storage conditions:

Do not seal receptacle gas tight.

Store in cool, dry conditions in well sealed receptacles.

Long-term value: 999 mg/m³, 400 ppm

Protect from heat and direct sunlight.

- · Storage class: -
- · 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

· Ingredients with limit values that require monitoring at the workplace:

· 8.1 Control parameters

106-9	97-8 butane, pure (10-20%)
	Short-term value: 1810 mg/m³, 750 ppm
	Long-term value: 1450 mg/m³, 600 ppm
	Carc (if more than 0.1% of buta-1.3-diene)
67-63	3-0 propan-2-ol (10-20%)
WEL.	Short-term value: 1250 mg/m³ 500 nnm

· DNELs

Hydrocarb	ons, C9-C11, n-alkanes, isoalkanes, cyclics,	<2% aromatics
Oral	DNEL,long term (chronic) - systemic effects	125 mg/kg bw/day (Consumer)
Dermal	DNEL,long term (chronic) - systemic effects	
		208 mg/kg bw/day (Employee)
Inhalative	DNEL,long term (chronic) - systemic effects	185 mg/m3 (Consumer)
		871 mg/m3 (Employee)

67-63-0 propan-2-ol

Oral	DNEL,long term (chronic) - systemic effects	26 mg/kg bw/day (Consumer)
Dermal	DNEL,long term (chronic) - systemic effects	319 mg/kg bw/day (Consumer)
		888 mg/kg bw/day (Employee)
Inhalative	DNEL,long term (chronic) - systemic effects	89 mg/m3 (Consumer)
		500 mg/m3 (Employee)

64742-95-6 Hydrocarbons, C9, aromatics

	· y ··· · · · · · · · · · · · · · · · · ·	
Oral	DNEL,long term (chronic) - systemic effects	11 mg/kg bw/day (Consumer)
Dermal	DNEL,long term (chronic) - systemic effects	11 mg/kg bw/day (Consumer)
		25 mg/kg bw/day (Employee)
Inhalative	DNEL,long term (chronic) - systemic effects	32 mg/m3 (Consumer)
		150 mg/m3 (Employee)

· PNECs

67-63-0 propan-2-ol

* *	
	140.9 mg/l (aquatic organism)
	140.9 mg/l (aquatic organism)
PNEC, fresh water sediment	552 mg/kg (aquatic organism)
PNEC, marine water sediment	552 mg/kg (aquatic organism)
PNEC,soil	28 mg/kg (terrestrial organism)

- · 8.2 Exposure controls
- · Individual protection measures, such as personal protective equipment
- General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Wash hands before breaks and at the end of work.

· Respiratory protection: Not required.

(Contd. on page 5)

Printing date 06.12.2022 Version: 1.2 (replaces version 1.1) Revision: 06.12.2022

(Contd. of page 4)

· Hand protection



If prolonged or repeated contact is likely, chemical resistant gloves are recommended.

- · Material of gloves Nitrile rubber, NBR
- Penetration time of glove material

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye/face protection



SECTION 9: Physical and chemical properties

· 9.1 Information on basic physical and chemical properties

· General Information

· Physical state Aerosol

• *Colour:* According to product specification

· Odour: Characteristic · Melting point/freezing point: Undetermined.

Boiling point or initial boiling point and boiling

range 82 °C

· Flammability Not applicable.

· Lower and upper explosion limit

 · Lower:
 0.7 Vol %

 · Upper:
 12 Vol %

 · Flash point:
 -97 °C

 · Auto-ignition temperature:
 365 °C

• **Decomposition temperature:** Not determined.

• pH Mixture is non-soluble (in water).

· Viscosity:

Kinematic viscosityDynamic:Not determined.Not determined.

·Solubility

• water: Not miscible or difficult to mix.

• Partition coefficient n-octanol/water (log value) Not determined. • Vapour pressure at 20 °C: 8,300 hPa

· Density and/or relative density

• **Density at 20 °C:** 0.66 g/cm³

9.2 Other information

· Appearance:

· Form: Aerosol

Important information on protection of health and environment, and on safety.

Explosive properties: Product is not explosive. However, formation of

explosive air/vapour mixtures are possible.

Change in condition

· Softening point/range

• Oxidising properties No further relevant information available.

• Evaporation rate Not determined.

· Information with regard to physical hazard classes

· Explosives Void · Flammable gases Void

(Contd. on page 6)

Printing date 06.12.2022 Version: 1.2 (replaces version 1.1) Revision: 06.12.2022

	(Contd. of page
· Aerosols	Extremely flammable aerosol. Pressurised container
	May burst if heated.
Oxidising gases	Void
Gases under pressure	Void
· Flammable liquids	Void
Flammable solids	Void
· Self-reactive substances and mixtures	Void
Pyrophoric liquids	Void
· Pyrophoric solids	Void
Self-heating substances and mixtures	Void
· Substances and mixtures, which emit flammable	
gases in contact with water	Void
Oxidising liquids	Void
· Oxidising solids	Void
· Organic peroxides	Void
· Corrosive to metals	Void
Desensitised explosives	Void

SECTION 10: Stability and reactivity

- · 10.1 Reactivity No further relevant information available.
- 10.2 Chemical stability Stable under recommended storage and handling conditions (see section 7).
- 10.3 Possibility of hazardous reactions

Dangerous reactions are not expected if the product is handled according to its intended use.

- · 10.4 Conditions to avoid No further relevant information available.
- · 10.5 Incompatible materials: No further relevant information available.
- · 10.6 Hazardous decomposition products: No decomposition if used according to specifications.

SECTION 11: Toxicological information

- · 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008
- · Acute toxicity

· LD/LC50	values rele	vant for classification:
Hydrocarb	ons, C9-C	11, n-alkanes, isoalkanes, cyclics, <2% aromatics
Oral	LD50	>5,000 mg/kg (rat)
Dermal	LD50	>5,000 mg/kg (rabbit)
Inhalative	LC50/4 h	>5,000 mg/l (rat)
106-97-8 b	utane, pui	re
Inhalative	LC50/4 h	658 mg/l (rat)
67-63-0 pr	opan-2-ol	
Oral	LD50	5,840 mg/kg (rat)
Dermal	LD50	13,900 mg/kg (rabbit)
Inhalative	LC50/6h	>25 mg/l (rat)
64742-95-	64742-95-6 Hydrocarbons, C9, aromatics	
Oral	LD50	2,000-5,000 mg/kg (rat)
Dermal	LD50	>2,000 mg/kg (rabbit)
. Carious an	a damaga	irritation Causes serious eve irritation

- · Serious eye damage/irritation Causes serious eye irritation.
- · STOT-single exposure May cause drowsiness or dizziness.
- · 11.2 Information on other hazards
- · Endocrine disrupting properties

None of the ingredients is listed.

GI

Version: 1.2 (replaces version 1.1) Printing date 06.12.2022 Revision: 06.12.2022

(Contd. of page 6)

SECTION 12: Ecological information

- · 12.1 Toxicity
- · Aquatic toxicity:

64742-95-6 Hydrocarbons, C9, aromatics

EC50, acute 1-10 mg/l (algae)

- · 12.2 Persistence and degradability No further relevant information available.
- · 12.3 Bioaccumulative potential No further relevant information available.
- · 12.4 Mobility in soil No further relevant information available.
- · 12.5 Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · vPvB: Not applicable.
- · 12.6 Endocrine disrupting properties

The product does not contain substances with endocrine disrupting properties.

- · 12.7 Other adverse effects
- Additional ecological information:
- · General notes: Harmful to aquatic organisms

SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
- · Uncleaned packaging:
- · Recommendation: Disposal must be made according to official regulations.

14.1 UN number or ID number		
ADR, IMDG, IATA	UN1950	
14.2 UN proper shipping name		
ADR	1950 AEROSOLS	
<i>IMDG</i>	AEROSOLS	
IATA	AEROSOLS, flammable	
14.3 Transport hazard class(es)		
ADR		
Class	2 5F Gases.	
Label	2.1	
IMDG, IATA		
2		
Class	2.1 Gases.	
Label	2.1 2.1	
14.4 Packing group	None.	
ADR, IMDG, IATA	Void	
14.5 Environmental hazards:	Not applicable.	
14.6 Special precautions for user	Warning: Gases.	

Printing date 06.12.2022 Version: 1.2 (replaces version 1.1) Revision: 06.12.2022

	(Contd. of page
Hazard identification number (Kemler co	ode): -
EMS Number:	F-D,S-U
Stowage Code	SW1 Protected from sources of heat.
· ·	SW22 For AEROSOLS with a maximum capacity of
	litre: Category A. For AEROSOLS with a capacity above
	1 litre: Category B. For WASTE AEROSOLS: Category
	C, Clear of living quarters.
Segregation Code	SG69 For AEROSOLS with a maximum capacity of
	litre:
	Segregation as for class 9. Stow "separated from" class
	except for division 1.4.
	For AEROSOLS with a capacity above 1 litre:
	Segregation as for the appropriate subdivision of class
	For WASTE AEROSOLS:
	Segregation as for the appropriate subdivision of class
14 # 3 # 14	
14.7 Maritime transport in bulk accordin	ng to IMO
14.7 Maritime transport in bulk accordin instruments	e g to IMO Not applicable.
<u>=</u>	
instruments	
instruments Transport/Additional information:	
instruments Transport/Additional information: ADR	Not applicable.
instruments Transport/Additional information: ADR Limited quantities (LQ)	Not applicable. IL
instruments Transport/Additional information: ADR Limited quantities (LQ)	Not applicable. IL Code: E0
instruments Transport/Additional information: ADR Limited quantities (LQ) Excepted quantities (EQ)	Not applicable. IL Code: E0 Not permitted as Excepted Quantity
instruments Transport/Additional information: ADR Limited quantities (LQ) Excepted quantities (EQ) Transport category	Not applicable. IL Code: E0 Not permitted as Excepted Quantity 2
instruments Transport/Additional information: ADR Limited quantities (LQ) Excepted quantities (EQ) Transport category Tunnel restriction code	Not applicable. IL Code: E0 Not permitted as Excepted Quantity 2
instruments Transport/Additional information: ADR Limited quantities (LQ) Excepted quantities (EQ) Transport category Tunnel restriction code IMDG	Not applicable. IL Code: E0 Not permitted as Excepted Quantity 2 D
instruments Transport/Additional information: ADR Limited quantities (LQ) Excepted quantities (EQ) Transport category Tunnel restriction code IMDG Limited quantities (LQ)	IL Code: E0 Not permitted as Excepted Quantity 2 D

SECTION 15: Regulatory information

- · 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · Seveso category P3a FLAMMABLE AEROSOLS
- Qualifying quantity (tonnes) for the application of lower-tier requirements 150 t
- Qualifying quantity (tonnes) for the application of upper-tier requirements 500 t
- 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

- H220 Extremely flammable gas.
- H225 Highly flammable liquid and vapour.
- H226 Flammable liquid and vapour.
- H280 Contains gas under pressure; may explode if heated.
- H304 May be fatal if swallowed and enters airways.
- H319 Causes serious eye irritation.
- H331 Toxic if inhaled.
- H335 May cause respiratory irritation.
- H336 May cause drowsiness or dizziness.
- H411 Toxic to aquatic life with long lasting effects.

(Contd. on page 9)

Printing date 06.12.2022 Version: 1.2 (replaces version 1.1) Revision: 06.12.2022

(Contd. of page 8)

EUH066 Repeated exposure may cause skin dryness or cracking.

· Abbreviations and acronyms:

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

DNEL: Derived No-Effect Level (UK REACH)

PNEC: Predicted No-Effect Concentration (UK REACH)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Flam. Gas 1A: Flammable gases - Category 1A

Aerosol 1: Aerosols - Category 1

Press. Gas (Comp.): Gases under pressure - Compressed gas

Flam. Liq. 2: Flammable liquids – Category 2 Flam. Liq. 3: Flammable liquids – Category 3

Acute Tox. 3: Acute toxicity - Category 3

Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

Asp. Tox. 1: Aspiration hazard – Category 1

Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard - Category 2

Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard - Category 3

* Data compared to the previous version altered.